

TECHNICAL DATA SHEET

Product Name: ANTIKA
Product type: Precast concrete paver & permeable
Application: •Residential - Vehicular & Pedestrian
 (e.g. driveways, patios)

Geometric characteristics

Nominal dimensions mm (in.):	height x width x length	(Dimensions include the joint spacer)
(All units are asymmetric)	60 x 65 x 83	(2 3/8 x 2 9/16 x 3 1/4)
	60 x 73 x 102	(2 3/8 x 2 7/8 x 4)
	60 x 76 x 80	(2 3/8 x 3 x 3 1/8)
	60 x 78 x 101	(2 3/8 x 3 1/16 x 4)
	60 x 85 x 139	(2 3/8 x 3 3/8 x 5 1/2)
	60 x 93 x 162	(2 3/8 x 3 11/16 x 6 3/8)
	60 x 101 x 136	(2 3/8 x 3 15/16 x 5 5/16)
	60 x 102 x 122	(2 3/8 x 4 x 4 13/16)
	60 x 105 x 142	(2 3/8 x 4 1/8 x 5 9/16)
	60 x 105 x 149	(2 3/8 x 4 1/8 x 5 7/8)
	60 x 111 x 150	(2 3/8 x 4 3/8 x 5 7/8)

Dimensional tolerances¹:

Length and width: -1.0 mm to + 2.0 mm.

Height: ± 3.0 mm.

Joint Width: Variable

Texture: Smooth and aged

Surface slip resistance: Slip-resistant surface texture

Approximate weight: Variable: 0.7 to 2.2 kg (1.6 to 4.8 lb)

Physical characteristics¹

Compressive strength: 50 MPa (min)

De-icing salt Freeze-thaw durability

Loss of mass after 28 cycles: 225 g/m² (max), or

Loss of mass after 49 cycles: 500 g/m² (max)

Surface Infiltration characteristics

Percent of open surface area: Variable

Surface Infiltration rate²: 25 227 mm/h (993 in./h)

Notes

1. Meets and exceeds the requirements of the CSA A231.2:19 "Precast concrete pavers" standard.
2. Initial post-construction surface Infiltration rate measured as per ASTM C 1781.

To learn more about the textures and colors for this product, please contact our representatives.