## **TECHNICAL DATA SHEET**

Product Name: EVA

Product type: Precast concrete paver

Application: •Residential - Vehicular & Pedestrian

(e.g. driveways, patios)

## **Geometric characteristics**

Nominal dimensions in. (mm): height x width x length (Dimensions include the joint spacer)

Unit A: 2 3/8 x 8 3/4 x 4 7/16 (60 x 223 x 112) Unit B: 2 3/8 x 8 3/4 x 8 3/4 Unit C: 2 3/8 x 8 3/4 x 13 3/16 (60 x 223 x 335)

Dimensional tolerances1:

Length and width:  $\pm 0.063$  in. (1.6 mm)

Height:  $\pm 0.125$  in. (3.2 mm)

Joint Width<sup>2</sup>: 1/8 in. (3 mm)

Surface slip resistance<sup>2</sup>: Slip-resistant surface texture

Approximate weight: Variable: 7.4 to 22.2 lb (3.4 to 10.1 kg)

Texture: Slate

Physical characteristics<sup>1</sup>

Compressive strength: 8000 psi (55 MPa)

Freeze-thaw durability

Loss of mass after 28 cycles: 225 g/m² (max), or Loss of mass after 49 cycles: 500 g/m² (max)

Water absorption: 5% max.

## Notes

- Meets and exceeds the requirements of the ASTM C 936 Standard Specification for Solid Concrete Interlocking Paving Units.
- 2 Meets the Americans with Disabilities Act (ADA) design guidelines for accessible paths:
  - Slip-resistance paver surface.
    - Paver joint openings do not allow the passage of a sphere greater than ½ in. (13 mm) in diameter

To learn more about the textures and colors for this product, please contact our representatives

www.techo-bloc.com November 2019