

## TECHNICAL DATA SHEET

**Product Name:** HEXA 100

**Product type:** Precast concrete paver

**Application:**

- ICl<sup>3</sup> - Light Vehicular traffic & Pedestrian  
(e.g. parking lots, terraces, parks)
- Residential - Vehicular & Pedestrian  
(e.g. driveways, patios)

### Geometric characteristics

**Nominal dimensions in. (mm):** height x width x length (Dimensions include the joint spacer)

Unit A: 3 15/16 x 9 x 15 3/16 (100 x 228 x 385)

**Dimensional tolerances<sup>1</sup>:**

Length and width: ± 0.063 in. (1.6 mm)

Height: ± 0.125 in. (3.2 mm)

**Joint Width<sup>2</sup>:** 3/32 in. (2.5 mm)

**Surface slip resistance<sup>2</sup>:** Slip-resistant surface texture

**Approximate weight:** 33.5 lb (15.2 kg)

**Texture:** HD<sup>2</sup> Smooth

### Physical characteristics<sup>1</sup>

**Compressive strength:** 8000 psi (55 MPa)

**Freeze-thaw durability**

Loss of mass after 28 cycles: 225 g/m<sup>2</sup> (max), or

Loss of mass after 49 cycles: 500 g/m<sup>2</sup> (max)

**Water absorption:** 5% max.

### Notes

1. Meets and exceeds the requirements of the ASTM C 936 Standard Specification for Solid Concrete Interlocking Paving Units.
2. Meets the Americans with Disabilities Act (ADA) design guidelines for accessible paths:
  - Slip-resistance paver surface.
  - Paver joint openings do not allow the passage of a sphere greater than ½ in. (13 mm) in diameter
3. Institutional, Commercial and Industrial.

*To learn more about the textures and colors for this product, please contact our representatives*