

TECHNICAL DATA SHEET

Product Name: TRAVERTINA RAW

Product type: Precast concrete paver & permeable

Application: •Residential - Vehicular & Pedestrian
(e.g. driveways, patios)

•Permeable

Geometric characteristics

Nominal dimensions in. (mm): height x length (Dimensions include the joint spacer)
Unit A: 2 3/4 x 4 7/16 x 11 (70 x 112 x 279)

Dimensional tolerances¹:
Length and width: ± 0.063 in. (1.6 mm)
Height: ± 0.125 in. (3.2 mm)

Joint Width²: 5/8 in. (15 mm)

Coefficient of Friction^{2,3}: Slip-resistant surface texture

Approximate weight: 91 lb (4.1 kg)

Texture: HD² Brushed Travertine

Physical characteristics¹

Compressive strength: 8000 psi (55 MPa)

Freeze-thaw durability
Loss of mass after 28 cycles: 225 g/m² (max), or
Loss of mass after 49 cycles: 500 g/m² (max)

Water absorption: 5% max.

Surface Infiltration characteristics

Percent of open surface area: 0.078

Surface Infiltration rate³: 793 in./h (20 150 mm/h)

Notes

1. Meets and exceeds the requirements of the ASTM C 936 Standard Specification for Solid Concrete Interlocking Paving Units.
2. Meets and exceeds the requirements of the ANSI A326.3 Standard test Method for measuring Dynamic Coefficient of Friction of Hard Surface Flooring Materials.
3. Initial post-construction surface Infiltration rate measured as per ASTM C 1781

To learn more about the textures and colors for this product, please contact our representatives