TECHNICAL DATA SHEET

Product Name: VALET

Product type: Precast concrete paver & permeable

Application: •Residential - Vehicular & Pedestrian

(e.g. driveways, patios)

Permeable

Geometric characteristics

Nominal dimensions mm (in.): height x width x length (Dimensions include the joint spacer)

Unit A: 60 x 165 x 165 (2 3/8 x 6 ½ x 6 ½)

Dimensional tolerances¹:

Length and width: -1.0 mm to + 2.0 mm.

Height: ± 3.0 mm.

Joint Width: 7 mm (9/32 in.)

Texture: Basalt

Surface slip resistance: Slip-resistant surface texture

Approximate weight: 3.7 kg (8.1 lb)

Physical characteristics¹

Compressive strength: 50 Mpa (min)

De-icing salt Freeze-thaw durability

Loss of mass after 28 cycles: 225 g/m² (max), or Loss of mass after 49 cycles: 500 g/m² (max)

Surface Infiltration characteristics

Percent of open surface area: 5.9%

Surface Infiltration rate²: 10 160 mm/h (400 in./h)

<u>Notes</u>

- Meets and exceeds the requirements of the CSA A231.2:19 "Precast concrete pavers" standard
- 2. Initial post-construction surface Infiltration rate measured as per ASTM C 1781.

To learn more about the textures and colors for this product, please contact our representatives.

www.techo-bloc.com November 2019