

## TECHNICAL DATA SHEET

**Product Name:** VICTORIEN 60 mm PERMEABLE  
**Product type:** Permeable precast concrete paver  
**Application:** •Residential - Vehicular & Pedestrian  
 (e.g. driveways, patios)  
 •Permeable

### Geometric characteristics

**Nominal dimensions in. (mm):** height x length (Dimensions include the joint spacer)  
 Unit A: 2 3/8 x 4 1/4 x 8 1/2 (60 x 108 x 216)  
**Dimensional tolerances<sup>1</sup>:**  
 Length and width: ± 0.063 in. (1.6 mm)  
 Height: ± 0.125 in. (3.2 mm)  
**Joint Width<sup>2</sup>:** 3/8 in. (10 mm)  
**Surface slip resistance<sup>2</sup>:** Slip-resistant surface texture  
**Approximate weight:** 6.9 lb (3.1 kg)  
**Texture:** Smooth

### Physical characteristics<sup>1</sup>

**Compressive strength:** 8000 psi (55 MPa)  
**Freeze-thaw durability**  
 Loss of mass after 28 cycles: 225 g/m<sup>2</sup> (max), or  
 Loss of mass after 49 cycles: 500 g/m<sup>2</sup> (max)  
**Water absorption:** 5% max.

### Surface Infiltration characteristics

Percent of open surface area: 0.096  
 Surface Infiltration rate<sup>3</sup>: 909 in./h (23 085 mm/h)

### Notes

1. Meets and exceeds the requirements of the ASTM C 936 Standard Specification for Solid Concrete Interlocking Paving Units.
2. Meets the Americans with Disabilities Act (ADA) design guidelines for accessible paths:
  - Slip-resistance paver surface.
  - Paver joint openings do not allow the passage of a sphere greater than ½ in. (13 mm) in diameter
3. Initial post-construction surface Infiltration rate measured as per ASTM C 1701

*To learn more about the textures and colors for this product, please contact our representatives*