

## TECHNICAL DATA SHEET

**Product Name:** PACIFIC SLAB  
**Product type:** Precast concrete slab  
**Application:** •Residential - Pedestrian only and at all times  
 (e.g. backyard patio)

### Geometric characteristics

<b>Nominal dimensions mm (in.):</b>	height x width x length (Dimensions include the joint spacer)	
	A: 1 3/16 x 9 7/16 x 6 5/16	(30 x 240 x 160)
	B: 1 3/16 x 9 7/16 x 9 7/16	(30 x 240 x 240)
	C: 1 3/16 x 9 7/16 x 12 5/8	(30 x 240 x 320)
<b>Dimensional tolerances<sup>1</sup>:</b>		
	Length and width:	
	Dimension ≤ 24 in. (610 mm):	-0.04 and +0.08 in. (-1.0 and +2.0 mm)
	Dimension > 24 in. (610 mm):	-0.06 and +0.12 in. (-1.5 and +3.0 mm)
	Height:	± 0.12 in. (±3.0 mm)
	Warpage:	
	Dimension ≤ 17.75 in. (450 mm):	±0.08 in. (±2.0 mm)
	Dimension > 17.75 in. (450 mm):	±0.12 in. (±3.0 mm)
<b>Joint Width:</b>	1/16 in	(2.0 mm)
<b>Texture:</b>	Smooth	
<b>Surface slip resistance:</b>	Slip-resistant surface texture	
<b>Approximate weight:</b>		
	A: 5.5 lb	(2.5 kg)
	B: 8.4 lb	(3.8 kg)
	C: 11.2 lb	(5.1 kg)
	Per Surface: 13.5 lb/ft <sup>2</sup>	(65.1 kg/m <sup>2</sup> )

### Physical characteristics<sup>1</sup>

**Flexural strength:** 725 psi (5.0 MPa)

#### **De-icing salt freeze-thaw durability**

Loss of mass after 28 cycles: 225 g/m<sup>2</sup> (max), or  
 Loss of mass after 49 cycles: 500 g/m<sup>2</sup> (max)

#### Notes

1. Meets and exceeds the requirements of the ASTM C 1782 Standard Specification for Utility Segmental Concrete Paving Slabs.

*To learn more about the textures and colors for this product, please contact our representatives.*