

**TECHNICAL DATA SHEET**

**Product Name:** TRAVERTINA RAW  
**Product type:** Precast concrete slab  
**Application:** •Residential - Pedestrian only and at all times  
 (e.g. backyard patio)

**Geometric characteristics**

Nominal dimensions mm (in.):		height x width x length (Dimensions include the joint spacer)
20 X 10:	57 x 508 x 254	(2 1/4 x 20 x 10)
20 X 20:	57 x 508 x 508	(2 1/4 x 20 x 20)
20 X 30:	57 x 508 x 762	(2 1/4 x 20 x 30)
30 X 30:	57 x 762 x 762	(2 1/4 x 30 x 30)
Dimensional tolerances <sup>1</sup> :		
Length and width:	-1.0 to +2.0 mm	
Height:	± 3.0 mm	
Warpage:		
Dimension ≤ 450 mm:	±2.0 mm	
Dimension > 450 mm:	±3.0 mm	
Joint Width:	2 mm	(1/16 in.)
Texture:	HD <sup>2</sup> Brushed Travertine	
Coefficient of Friction <sup>2</sup> :	0.66	
Approximate weight:		
20 X 10:	16.2 kg	(35.7 lb)
20 X 20:	32.4 kg	(71.4 lb)
20 X 30:	48.5 kg	(106.9 lb)
30 X 30:	72.8 kg	(160.5 lb)
Per Surface:	125.6 kg/m <sup>2</sup>	(25.7 lb/ft <sup>2</sup> )

**Physical characteristics<sup>1</sup>**

**Flexural strength:** 5.0 MPa (min)  
**De-icing salt freeze-thaw durability**  
 Loss of mass after 28 cycles: 225 g/m<sup>2</sup> (max), or  
 Loss of mass after 49 cycles: 500 g/m<sup>2</sup> (max)

**Notes**

1. Meets and exceeds the requirements of the CSA A231.1:19 "Precast concrete paving slabs" standard.
2. Meets and exceeds the requirements of the ANSI A326.3 Standard test Method for measuring Dynamic Coefficient of Friction of Hard Surface Flooring Materials.

*To learn more about the textures and colors for this product, please contact our representatives.*